

# Miscellaneous accessories

## Aluminium adhesive tape ALU-BT or ALU-HT

Roll of adhesive aluminium tape  
width = 50 mm / length = 50 m +/- 10%  
Temperature range : ALU/BT : 105°C - ALU/HT : 200°C



## Adhesive tape POLY50 and FIV 200

Adhesive tape for heat cables strapping  
width = 19 mm / length = 50 m +/- 10%  
POLY 50 : polyester / maxi 60°C  
FIV 200 : armed fiber glass / maxi 150°C



## Modular electrical boxes CE 001 to CE 003

Pre assembled modular electric box  
CE 001 = Circuit breaker 16 Amps + differential 30mA  
CE 002 = Circuit breaker 25 Amps + differential 30mA  
+ Electronic temperature regulator REG 150  
+ power contactor : ask for request



## Temperature sensor PT1000 - length 2m

Temperature sensor PT1000 for electronic Novatrace box  
Flexible cable 2m / 0.75 mm<sup>2</sup> (other length on request)  
Water proof sensor IP x4 / Gland M20 included  
Available for ambient sensor or surface temperature  
for the electronic thermostats THA/E or THE/S.



## Output insulation and fixing tube for boxes T/SCS

Polycarbonate tube allowing direct fixing on process pipe  
of all boxes and thermostats :  
BJK/S, THA/C, THA/E, THS/S,....  
Direct entries of 3 or 4 heating cables.  
For pipe diam >20 mm / maxi temperature exposure 100°C.  
Height from baseplate / tube : 30/120 mm / M32



## Digital insulation tester

Digital insulation tester  
delivered in a storage case with  
2 connecting cables and crocs clips  
Insulation resistance mesure under 250 / 500 and 1000 Volts  
Measurement hold function (Hold)



[www.heating-cables.com](http://www.heating-cables.com)

[info@technitrace.fr](mailto:info@technitrace.fr)



[www.novatrace.com](http://www.novatrace.com)

[www.heating-cables-technitrace.com](http://www.heating-cables-technitrace.com)

# Miscellaneous accessories

## Connection sets for normal zones.

Complete connexion set CAxT  
for self regulating heating cables CABT, CAMT & CAHT  
Thermo retractable 3/1 and 12/4 + gland M20



## ATEX/EEEx 'e' connection set

Complete connexion set for hazardous area  
(increased security) Eex'e'  
for self regulating heating cables  
CABT/Ex & CAHT/Ex



## ATEX/EEEx 'd' connection set

Complete connexion set for hazardous area  
(explosion proof security) Eex'd'  
for self regulating heating cables  
CABT/Ex & CAHT/Ex



**Other accessories available**  
**Do not hesitate to contact our technical departement**

## Virtual presentation on USB key

USB key which includes a virtual presentation animation  
of Techitrace company.  
Included all installation videos for all  
connexion kits.



# Miscellaneous accessories

## Through insulation kit SC/CAxT

Perforated stainless steel plate  
Gland + gasket + nut  
SC/CAxT : for all self regulating heating cables



## Through insulation into flexible SC/FLEX

Perforated stainless steel plate  
Flexible grooved sheath length 500 mm  
+ 2 end fittings + 2 nuts



## Stainless steel fixing bracket EQ/FIX

Stainless steel folded fixing bracket  
for supporting  
BJK/S, BJK/RR, THA/C, THS, ...



## Voltage indicator lamp

Voltage indicator lamp for the front panel  
VOY230 for 230 V supply voltage or  
VOY400 for 400 V supply voltage  
opening 10 mm wide + bold.



## Self adhesive caution label ETI

Potential danger warning label  
black text on yellow background  
ELECTRIC HEAT TRACING  
Self adhesive



## Spare thermostatic insert

Printed circuit board with thermostatic insert  
for the replacement of surface thermostat  
THS/S or THS/SS  
Temperature available : 0-100°C or 50°C-250°C



[www.heating-cables.com](http://www.heating-cables.com)

[info@technitrace.fr](mailto:info@technitrace.fr)



[www.novatrace.com](http://www.novatrace.com)

[www.heating-cables-technitrace.com](http://www.heating-cables-technitrace.com)